



**NOTES:**

1. DISPLACEMENT PER REVERLUTION PER STAGE = 20.0 CC/REV
2. DISPLACEMENT AT 1000 RPM = 20.0 LT/MIN
3. PRV CRACKING PRESSURE:-  
 MINIMUM = 2.9 BAR (42 PSI)  
 MAXIMUM = 8.27 BAR (120PSI)
4. FOR EACH FULL TURN OF THE ADJUSTER THE CRACKING PRESSURE WILL INCREASE/DECREASE BY 0.25 BAR (3.6 PSI)

 COPYRIGHT (c) 2013 AT POWER LTD UNIT 9, CHESTNUT DRIVE, WYMONDHAM, NORFOLK, UK, NR18 9SB  <small>UNLESS OTHERWISE STATED:          DIMENSIONS IN MILLIMETRES          TOLERANCES: LINEAR ± 0.1 ANGULAR ± 0.5°          SURFACE FINISH √ = √          DRAWING STANDARDS TO ATQS 6003          DATE FORMAT: DD/MM/YY</small>  <small>THIS DESIGN IS THE PROPERTY OF          AT POWER THROTTLES LTD AND          MUST NOT BE REPRODUCED OR          COMMUNICATED WITHOUT          AUTHORITY</small>	 THIRD ANGLE PROJECTION		MATERIAL SEE COMPONENT PARTS
	SCALE 1:2	WEIGHT 3.1 kg	FINISH SEE COMPONENT PARTS
	DRAWN- S.HOW		DRAWING TITLE <b>3 STAGE CORDIS-PRESSURE PUMP-SHORT NOSE-20.1 Lt</b>
	DATE - 22/12/17		DRAWING NUMBER <b>104-103-00089</b>
CHECKED - S.HOW		SHEET 2 OF 2 A3	
APPROVED - A.CLIFTON			